



AUTOMOTIVE TOOLS



POWER CLEAN™ FLUSH TOOL

CLEANS ENGINE COOLING SYSTEMS COMPLETELY AND THOROUGHLY

Inadequate flushing can ruin a newly installed water pump and result in warranty problems and frustrated customers. Perform a complete cooling system flush by using clean water and compressed air. The Power Clean™ Flush Tool “water hammers” accumulated sludge and scale deposits without the use of harsh chemicals or solvents. It cleans radiators, heat exchangers, hoses and engine blocks more effectively than conventional flushes, maintains system integrity and ensures warranty coverage on replacement parts, including water pumps. The Power Clean™ Flush Tool’s patented process uses fixed dimensional control of the air and liquid flow paths. The process allows air to pressurise the water creating a pulsating action to scrub deep into corners and crevices, eliminating trapped debris.

- > Pulsating gun assembly with pre-set regulator
- > Water line backflow preventer
- > Large rubber tip for radiator necks and direct flushing of the engine block
- > Small rubber tip on whip hose for direct access to heater core tube stubs.
- > 1.6cm and 1.9cm heater hose barbs for flushing heater cores or engine blocks
- > Durable protective storage case with room for additional items

Part Numbers:

91002 - Power Clean™ Flush Tool

91002-9 - Power Clean™ Accessory - Heavy Duty Cone



COOLANT & BATTERY REFRACTOMETER

MEASURES CONCENTRATION OF COOLANT MIXTURE IN ENGINE

Place small sample of coolant on lens, then hold lens up to light source. Light bends through liquid, providing an accurate reading on scale.

- > Measuring coolant concentrations is essential to cooling system maintenance
- > Most technicians use hydrometers to test coolant concentration via gravity or floating ball scales
- > Hydrometers must be temperature corrected, and may give false readings when testing new, propylene-based coolants
- > Gates refractometer automatically corrects for temperature on both types of coolant [ethylene and propylene glycol] while measuring battery charge levels

Part Number: 91001

AUTOMOTIVE TOOLS

HAND-HELD HOSE CUTTER & REPLACEMENT BLADES

MAKES CLEAN CUTS WITH NO RAGGED EDGES

Cuts most non-metal reinforced rubber hoses up to 75mm I.D. Excellent for cutting thin walled flexible pipe, PE and PVC pipe (up to 38mm) used in sprinkler systems.

- > Hand held hose cutter and blades
- > Lightweight with nylon handles
- > Blade closes into handle for safety
- > Use small cutter for hoses up to 38mm I.D.
- > Packaging: Cutter and blades individually packaged on shrink-wrapped cards ready for pegboard display

Part Numbers:

91143 - Large I.D. Hose Cutter

91144 - Large I.D. Cutter Replacement Blade

91153 - Small I.D. Cutter

91154 - Small I.D. Cutter Replacement Blade

FLEXI DRIVER

ALLOWS FOR EASY INSTALLATION OF HOSE CLAMPS IN CONFINED SPACES

- > Flexible shaft and non slip handle provides 90 degree access and works best in hard to reach places.
- > Hex head allows for easy clamp installation

PART NUMBERS:

GFD-1 - 6mm & 8mm interchangeable socket
- Suitable for Perforated band hose clamps

GFD-3 - 6mm & 7mm interchangeable socket
- Suitable for Non Perforated band hose clamps

COOLING SYSTEM PRESSURE TESTER

CONTAINS ALL THE COMPONENTS NEEDED TO CHECK COOLING SYSTEMS AND RADIATOR CAPS

- > Lightweight, impact resistant analyser
- > Pressure release button on easy to read gauge allows for safe venting of system during testing. This is a precision instrument designed to locate leaks and pressure cooling system problems.
- > The gauge includes cap testing, pressure ranges 17-19lbs, 20lbs and 28lbs.
- > The head also includes a pressure release bar to allow the release of pressure build up before moving from neck.
- > Packaging: Individually boxed.

Part Number: 12270



Scan to find out more on
Gates Automotive Tools.



GATES AUSTRALIA PTY LTD

1-15 Hydrive Close, Dandenong South, Victoria, 3175

PH: +61 3 9797 9666 FAX: +61 3 9797 9600

www.GatesAustralia.com.au